

Enclosures PwrPak7D-E1™



COMPACT DUAL ANTENNA ENCLOSURE DELIVERS NOVATEL'S LEADING SPAN® GNSS+INS TECHNOLOGY



DUAL ANTENNA INPUT

Multi-frequency, dual antenna input allows the PwrPak7D-E1 to harness the power of NovAtel CORRECT™ with RTK and ALIGN functionality. This makes the PwrPak7D-E1 ideal for ground vehicle, marine or aircraft based systems, providing industry leading GNSS multi-constellation heading and position data in static and dynamic environments.

SPAN: WORLD LEADING GNSS+INS TECHNOLOGY

Synchronous Position, Attitude and Navigation (SPAN) technology brings together two different but complementary technologies: Global Navigation Satellite System (GNSS) positioning and inertial navigation. The absolute accuracy of GNSS positioning and the stability of Inertial Measurement Unit (IMU) gyro and accelerometer measurements are tightly coupled to provide an exceptional 3D navigation solution that is stable and continuously available, even through periods when satellite signals are blocked.

SPAN ENABLED MEMS RECEIVER

The PwrPak7D-E1 contains an Epson G320N MEMS IMU to deliver world class NovAtel SPAN technology in an integrated, single box solution. This product is commercially exportable and provides an excellent price/performance/size GNSS+INS solution.

FUTURE PROOFED SCALABILITY

Capable of tracking all present and upcoming GNSS constellations and satellite signals, the PwrPak7D-E1 is a robust, high precision receiver that is software upgradable in the field to provide the custom performance required for your application demands.

The PwrPak7D-E1 has a powerful OEM7® GNSS engine, integrated MEMS IMU, built in Wi-Fi, on board NTRIP client and server support, and 16 GB of internal storage.

PRECISE THINKING MAKES IT POSSIBLE

Our GNSS products have set the standard in quality and performance for over 20 years. State-of-the-art, lean manufacturing facilities in our North American headquarters produce the industry's most extensive line of OEM receivers, antennas and subsystems.

FEATURES

- + SPAN enabled enclosure featuring NovAtel's tightly coupled GNSS+INS engine
- + Enhanced connection options including serial, USB, CAN and Ethernet
- + 555 channel, all-constellation, multi-frequency positioning solution
- + Multi-channel L-Band supports TerraStar correction services
- + Multiple communication interfaces for easy integration and installation
- + Built-in Wi-Fi support
- + 16 GB of internal storage
- + ALIGN® heading solution

If you require more information about our enclosures, visit www.novatel.com/products/gnss-receivers/enclosures

PwrPak7D-E1™



PERFORMANCE¹

Channel Configuration

555 Channels

Signal Tracking

Primary RF²

GPS L1 C/A, L1C, L2C, L2P, L5

GLONASS³ L1 C/A, L2 C/A, L2P,

L3, L5

BeiDou⁴ B1, B2

Galileo E1, E5 AltBOC, E5a, E5b

NavIC (IRNSS) L5

SBAS L1, L5

QZSS L1 C/A, L1C, L2C, L5

L-Band up to 5 channels

Secondary RF²

GPS L1 C/A, L1C, L2C, L2P, L5

GLONASS³ L1 C/A, L2 C/A, L2P,

L3, L5

BeiDou⁴ B1, B2

Galileo E1, E5 AltBOC, E5a, E5b

NavIC (IRNSS) L5

QZSS L1 C/A, L1C, L2C, L5

Horizontal Position Accuracy (RMS)

Single point L1 1.5 m

Single point L1/L2 1.2 m

NovAtel CORRECT™

» SBAS⁵ 60 cm

» DGPS 40 cm

» PPP⁶

TerraStar-L 40 cm

TerraStar-C 4 cm

» RTK 1 cm + 1 ppm

Initial time <10 s

Initial reliability >99.9%

Maximum Data Rate

GNSS Measurements up to 20 Hz

GNSS Position up to 20 Hz

INS Position/Attitude up to 20 Hz

IMU Raw Data Rate 125 Hz

Time to First Fix

Cold start^{7,8} <40 s

Hot start^{9,8} <19 s

Time Accuracy¹⁰ 20 ns RMS

Velocity Limit¹¹ 515 m/s

IMU PERFORMANCE¹²

Gyroscope Performance

Input range ±150 deg/s

Rate bias stability 3.5 deg/hr

Angular random walk

0.1 deg/√hr

Accelerometer Performance

Range ±5 g

Bias stability 0.1 mg

Velocity random walk

0.5 m/s/√hr

COMMUNICATION PORTS

1 RS-232 up to 460,800 bps

2 RS-232/RS-422 selectable

up to 460,800 bps

1 USB 2.0 (device) HS

1 USB 2.0 (host) HS

1 Ethernet 10/100 Mbps

1 CAN Bus 1 Mbps

3 Event inputs

3 Event outputs

1 Pulse Per Second output

1 Quadrature Wheel Sensor

input

PHYSICAL AND ELECTRICAL

Dimensions 147 x 125 x 55 mm

Weight 510 g

Power

Input voltage +9 to +36 VDC

Power consumption¹³ 1.8 W

2 Antenna LNA Power Outputs

Output voltage 5 VDC ±5%

Maximum current 200 mA

Connectors

2 Antenna SMA

USB device Micro A/B

USB host Micro A/B

Serial, CAN, Event I/O

DSUB HD26

Ethernet RJ45

Data Logging Push button

Power SAL M12, 5 pin, male

Status LEDs

Power

GNSS

INS

Data Logging

USB

ENVIRONMENTAL

Temperature

Operating -40°C to +75°C

Storage -40°C to +95°C

Humidity 95% non-condensing

Waterproof IEC 60529 IPX7

Dust IEC 60529 IP6X

Vibration (operating)

Random MIL-STD-810 514.6

Category 24, 20g RMS

Sinusoidal IEC 60068-2-6

Acceleration (operating)

MIL-STD 810G, Method 513.6

Procedure II (16 g)

Bump ISO 9022-31-06 (25g)

Shock (non-operating)

MIL-STD-810G, 516.6,

Procedure 1,

40 g 11 ms terminal sawtooth

Compliance

FCC, IC, CE

Industry Canada, RoHS, WEEE

INCLUDED ACCESSORIES

- Power cable
- USB cable
- DSUB HD26 to DB9 RS-232 cable

OPTIONAL ACCESSORIES

- Full breakout cable for DSUB HD26 connector
- DSUB HD26 to M12 IMU cable
- RJ45 Ethernet cable
- VEXXIS® GNSS-500 and GNSS-800 series antennas
- ANT series antennas
- GrafNav/GravNet®
- Inertial Explorer®
- NovAtel Connect

For the most recent details of this product:

www.novatel.com/products/gnss-receivers/enclosures/pwrpak7D-E1

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada) or 403-295-4900

China 0086-21-68882300

Europe 44-1993-848-736

SE Asia and Australia

61-400-883-601

Version 1 Specifications subject to change without notice.

©2018 NovAtel Inc. All rights reserved.

NovAtel, PwrPak7, OEM7, SPAN, VEXXIS, GrafNav, GrafNet, Inertial Explorer and ALIGN are registered trademarks of NovAtel Inc.

NovAtel CORRECT and RTK ASSIST are trademarks of NovAtel Inc.

Printed in Canada.

D22921 March 2018



PERFORMANCE DURING GNSS OUTAGES¹

Outage Duration	Positioning Mode	POSITION ACCURACY (M) RMS		VELOCITY ACCURACY (M/S) RMS		ATTITUDE ACCURACY (DEGREES) RMS		
		Horizontal	Vertical	Horizontal	Vertical	Roll	Pitch	Heading
0 s	RTK ¹⁵	0.02	0.03	0.020	0.015	0.020	0.020	0.090
	SP	1.00	0.60	0.020	0.015	0.020	0.020	0.090
	PP ¹⁶	0.01	0.02	0.015	0.010	0.008	0.008	0.038
10 s	RTK ¹⁵	0.25	0.15	0.065	0.025	0.040	0.040	0.130
	SP	1.25	0.70	0.065	0.025	0.040	0.040	0.130
	PP ¹⁶	0.01	0.02	0.015	0.010	0.008	0.008	0.038

¹ Typical values. Performance specifications subject to GNSS system characteristics, Signal-In-Space (SIS) operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.

² Model-configurable to track L5/E5a (all / Galileo) through L2 (GPS) or L3/E5b/B2 (GLONASS / Galileo / BeiDou) through L2 (GLONASS). See manual for details.

³ Hardware ready for L3 and L5.

⁴ Designed for BeiDou Phase 2 and 3, B1 and B2 compatibility.

⁵ GPS only.

⁶ Requires a subscription to a TerraStar data service. Subscriptions available from NovAtel.

⁷ Typical value. No almanac or ephemerides and no approximate position or time.

⁸ Available in Q2 2018.

⁹ Typical value. Almanac and recent ephemerides saved and approximate position and time entered.

¹⁰ Time accuracy does not include biases due to RF or antenna delay.

¹¹ Export licensing restricts operation to a maximum of 515 metres per second, message output impacted above 500 m/s.

¹² Supplied by IMU manufacturer.

¹³ Typical value. Consult the OEM7 Family Installation & Operation User Manual for power supply considerations.